

## 使用安全荷重

6 × 24 A種 J I S G 3525

| 公称径 | ストレート |       | チヨーク |       | 2本吊り |       | 3,4本吊り |       |
|-----|-------|-------|------|-------|------|-------|--------|-------|
|     | kn    | tf    | kn   | tf    | 60度  |       | 60度    |       |
| mm  |       |       |      |       | kn   | tf    | kn     | tf    |
| 6   | 2.95  | 0.301 | 2.21 | 0.226 | 5.09 | 0.519 | 7.63   | 0.778 |
| 8   | 5.27  | 0.537 | 3.95 | 0.403 | 9.08 | 0.926 | 13.6   | 1.39  |
| 9   | 6.65  | 0.678 | 4.99 | 0.509 | 11.5 | 1.17  | 17.2   | 1.75  |
| 10  | 8.22  | 0.838 | 6.16 | 0.628 | 14.2 | 1.45  | 21.3   | 2.17  |
| 12  | 11.8  | 1.21  | 8.88 | 0.905 | 20.4 | 2.08  | 30.6   | 3.12  |
| 14  | 16.1  | 1.64  | 12.1 | 1.23  | 27.8 | 2.83  | 41.6   | 4.25  |
| 16  | 21.0  | 2.14  | 15.8 | 1.61  | 36.2 | 3.69  | 54.3   | 5.54  |
| 18  | 26.7  | 2.72  | 20.0 | 2.04  | 46.0 | 4.69  | 69.0   | 7.03  |
| 20  | 32.8  | 3.35  | 24.6 | 2.51  | 56.6 | 5.77  | 84.9   | 8.66  |
| 22  | 39.8  | 4.06  | 29.9 | 3.05  | 68.7 | 7.01  | 103    | 10.5  |
| 24  | 47.3  | 4.83  | 35.5 | 3.62  | 81.6 | 8.32  | 122    | 12.5  |
| 26  | 55.5  | 5.66  | 41.6 | 4.24  | 95.7 | 9.76  | 144    | 14.6  |
| 28  | 64.5  | 6.58  | 48.4 | 4.93  | 111  | 11.3  | 167    | 17.0  |
| 30  | 74.0  | 7.55  | 55.5 | 5.66  | 128  | 13.1  | 191    | 19.5  |
| 32  | 84.2  | 8.58  | 63.1 | 6.44  | 145  | 14.8  | 218    | 22.2  |
| 36  | 107.0 | 10.90 | 79.9 | 8.14  | 184  | 18.8  | 275    | 28.1  |
| 40  | 132.0 | 13.40 | 98.6 | 10.10 | 227  | 23.1  | 340    | 34.7  |