





平行より

①

構成	6×Fi (29)	6×WS (31)	6×WS (36)	6×WS (41)
繊維心				
呼び	フィラー形	ウォーリントンシール形	ウォーリントンシール形	ウォーリントンシール形
	29本線6より	31本線6より	36本線6より	41本線6より

公称径	最外外層素線径				標準断面積	切断荷重		単位質量
	Fi (29)	WS (31)	WS (36)	WS (41)		裸・めっき		
						B種		
mm	mm	mm	mm	mm	mm ²	kn	tf	kg/m
8	0.46				27.5	37.9	3.86	0.253
9	0.52				34.7	48.0	4.89	0.321
10	0.58				42.9	59.2	6.04	0.396
11.2	0.65				53.8	74.3	7.58	0.496
(12)	0.69				61.8	85.1	8.68	0.570
12.5	0.72				67.0	92.5	9.43	0.618
14	0.81				84.1	116	11.8	0.776
16	0.93	1.04	0.93		110	152	15.5	1.01
18	1.04	1.17	1.04		139	192	19.6	1.28
20	1.16	1.30	1.14	1.01	172	237	24.2	1.58
(22)	1.28	1.43	1.26	1.12	208	286	29.2	1.92
22.4	1.30	1.45	1.28	1.14	215	297	30.3	1.99
(24)	1.40	1.56	1.37	1.22	247	340	34.7	2.28
25	1.45	1.62	1.43	1.80	268	370	37.7	2.47
(26)	1.60	1.68	1.47	1.32	290	399	40.7	2.68
28	1.62	1.82	1.60	1.43	336	464	47.3	3.10
30	1.74	1.95	1.71	1.55	386	533	54.4	3.56
31.5	1.82	2.04	1.80	1.63	426	588	60.0	3.93
(32)	1.85	2.08	1.83	1.63	426	605	61.7	4.06
33.5	1.94	2.17	1.91	1.73	481	665	67.8	4.44
(34)	1.97	2.20	1.94	1.73	496	684	69.7	4.58
35.5	2.06	2.30	2.02	1.83	541	746	76.1	4.99
(36)	2.10	2.34	2.06	1.83	556	766	78.1	5.13
37.5	2.17	2.43	2.14	1.94	603	833	94.9	5.57
(38)	2.20	2.48	2.17	1.94	620	853	87.0	5.72
40	2.32	2.60	2.28	2.06	686	948	96.7	6.33
42.5	2.46	2.76	2.42	2.19	775	1,070	109	7.15
45	2.61	2.92	2.57	2.32	869	1,200	122	8.01
47.5	2.75	3.08	2.71	2.45	968	1,340	137	8.93
50	2.90	3.25	2.85	2.58	1,070	1,480	151	9.90
53	3.07	3.44	3.02	2.73	1,210	1,660	169	11.1
56	3.24	3.63	3.19	2.89	1,350	1,860	190	12.4
60	3.47	3.89	3.42	3.10	1,540	2,130	217	14.2

公称径()はJIS準拠