


## 交差より



構成	6 × 37 (JIS G 3525)
呼び	37本線6より

公称径	最外層素線径	標準断面積	切断荷重				単位質量
			めっき		裸		
			G種		A種		
mm	mm	mm <sup>2</sup>	kn	tf	kn	tf	kg/m
6	0.28	14.2	17.8	1.82	19.1	1.95	0.129
8	0.38	25.3	31.6	3.22	34.0	3.47	0.230
9	0.43	32.0	40.0	4.08	43.0	4.38	0.291
10	0.47	39.5	49.4	5.04	53.1	5.41	0.359
12	0.57	56.9	71.1	7.25	76.5	7.80	0.517
14	0.66	77.4	96.7	9.86	104	10.6	0.704
16	0.76	101	126	12.9	136	13.9	0.920
18	0.85	128	160	16.3	172	17.5	1.16
20	0.95	158	197	20.1	212	21.6	1.44
22	1.04	191	239	24.4	257	26.2	1.74
24	1.14	228	284	29.0	306	31.2	2.07
26	1.23	267	334	34.1	359	36.6	2.43
28	1.32	310	387	39.5	416	42.4	2.82
30	1.42	356	444	45.3	478	48.7	3.23
32	1.51	404	505	51.5	544	55.5	3.68
36	1.70	512	640	65.3	688	70.2	4.66
40	1.89	632	790	80.6	850	86.7	5.75
44	2.08	765	956	97.5	1030	105	6.96
48	2.27	910	1,140	116	1220	124	8.28
52	2.46	1,070	1,330	136	1440	147	9.72
56	2.65	1,240	1,550	158	1670	170	11.30
60	2.84	1,420	1,780	182	1910	195	12.90