

使用安全荷重

6 × 37 A種 JIS G 3525

公称径	ストレート		チョーク		2本吊り		3,4本吊り	
					60度		60度	
mm	kn	tf	kn	tf	kn	tf	kn	tf
6	3.18	0.325	2.39	0.243	5.49	0.560	8.23	0.84
8	5.67	0.578	4.25	0.433	9.77	0.996	14.7	1.49
9	7.17	0.731	5.38	0.548	12.4	1.26	18.5	1.89
10	8.85	0.902	6.64	0.677	15.3	1.56	22.9	2.33
12	12.8	1.30	9.56	0.975	22.0	2.24	33.0	3.36
14	17.3	1.77	13.0	1.33	29.9	3.05	44.8	4.57
16	22.7	2.31	17.0	1.73	39.1	3.99	58.6	5.98
18	28.7	2.92	21.5	2.19	49.4	5.04	74.1	7.56
20	35.3	3.60	26.5	2.70	60.9	6.21	91.4	9.32
22	42.8	4.37	32.1	3.28	73.9	7.53	111	11.3
24	51.0	5.20	38.3	3.90	87.9	8.97	132	13.4
26	59.8	6.10	44.9	4.58	103	10.5	155	15.8
28	69.3	7.07	52.0	5.30	120	12.2	179	18.3
30	79.7	8.12	59.8	6.09	137	14.0	206	21.0
32	90.7	9.25	68	6.93	156	15.9	234	23.9
36	115	11.7	86	8.77	198	20.2	297	30.2
40	142	14.4	106	10.8	244	24.9	366	37.4
44	172	17.5	129	13.1	296	30.2	444	45.3
48	203	20.7	153	15.6	351	35.7	526	53.6
52	240	24.5	180	18.4	414	42.2	621	63.3
56	278	28.4	209	21.3	480	48.9	720	73.4
60	318	32.5	239	24.3	549	56.0	823	84.0