

# 柔ら~かいワイヤロープ

使用安全荷重

公称径	破断荷重		ストレート		チョーク		2本吊り		3,4本吊り	
							60度		60度	
mm	kn	tf	kn	tf	kn	tf	kn	tf	kn	tf
12	76	7.75	12.7	1.30	9.5	0.97	21.8	2.22	32.8	3.34
14	104	10.6	17.3	1.76	13.0	1.33	29.9	3.05	44.8	4.57
16	136	13.9	22.7	2.31	17.0	1.73	39.0	3.98	58.6	5.98
18	172	17.5	28.7	2.93	21.5	2.19	49.4	5.04	74.1	7.56
20	212	21.6	35.3	3.60	26.5	2.70	60.9	6.21	91.4	9.32
24	306	31.2	51.0	5.20	38.3	3.90	87.9	8.96	132	13.5
26	448	45.7	74.7	7.62	56.0	5.71	129	13.2	193	19.7
28	519	52.9	86.5	8.82	64.9	6.62	149	15.2	224	22.8
32	678	69.1	113	11.5	84.8	8.65	195	19.9	292	29.8
36	859	87.6	143	14.6	107	10.9	247	25.2	370	37.7
40	1,040	106	173	17.6	130	13.3	299	30.5	448	45.7
45	1,320	135	220	22.4	165	16.8	379	38.6	569	58.0
50	1,630	166	272	27.7	204	20.8	468	47.7	703	71.7
55	1,970	201	328	33.4	246	25.1	566	57.7	849	86.6
60	2,330	238	388	39.6	291	29.7	670	68.3	1,004	102.0
70	3,170	323	528	53.8	396	40.4	911	92.9	1,366	139.0